


VERT-2-GO X-PURE GEL

1. IDENTIFICATION	
Product name	: VERT-2-GO X-PURE GEL
Product code	: 09-12460
Supplier	: Wood Wyant Canada Inc. A division of Sani-Marc Group 42, rue de l'Artisan Victoriaville, Québec G6P 7E3 1-819-758-1541
Manufacturer	: Wood Wyant Canada Inc. A division of Sani-Marc Group 42, rue de l'Artisan Victoriaville, Québec G6P 7E3 1-819-758-1541
Identified uses	: Special: Hand Sanitizer
Uses advised against	: Only use this product as directed. Read label before using.
Date of issue (YYYY-MM-DD)	: 2023-01-31
In case of emergency : Emergency phone: CANUTEC (613) 996-6666 (Collect calls accepted)	

2. HAZARDS IDENTIFICATION	
Information in this section only concerns the product as supplied. Contact your account manager to get more information on diluted form hazards identification.	
Product Classification	: FLAMMABLE LIQUIDS - Category 2 EYE IRRITATION - Category 2B
Signal word	: Danger
Hazard pictograms	: 
Hazard statements	: Highly flammable liquid and vapors. Causes eye irritation.
<u>Precautionary statements</u>	
General	: Highly flammable liquid and vapors. Handle with care. Read label before use.
Prevention	: Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wash thoroughly after handling.
Response	: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
Storage	: Not applicable.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: No additional information.
Other hazards which do not result in classification	: None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/mixture : Mixture

Name	CAS number	% (w/w)
Ethanol	64-17-5	60 - 80
Isopropyl alcohol	67-63-0	1 - 5

Occupational exposure limits, if available, are listed in Section 8.

4. FIRST AID MEASURES

Description of required first aid measures

Eye contact In case of contact with eyes, flush with fresh water. Check for and remove any contact lenses. Continue rinsing. If irritation persists, get medical attention.

Skin contact In case of irritation, rinse with water. Get medical attention if irritation persists.

Ingestion Rinse mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Inhalation Move victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if adverse health effects persist or are severe. Maintain an open airway.

Most important symptoms/effects, acute and delayed

Eye contact Adverse symptoms may include the following:
irritation
watering
redness

Skin contact No specific symptoms under normal use conditions.

Ingestion No specific symptoms under normal use conditions.

Inhalation No specific symptoms under normal use conditions.

Notes to physician Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

See toxicological information (Section 11)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media Do not use water jet.

Specific hazards arising from the chemical Highly flammable liquid and vapors. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

Special fire-fighting procedures Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action should be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Initiate spill response procedures if required.

Personal protection Put on appropriate personal protective equipment (see Section 8).

Cleaning method Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Use a water rinse for final clean-up.

7. HANDLING AND STORAGE

Handling	Use in a way to prevent food contamination. Follow label instructions for use.
Storage and Incompatibility	Store in accordance with local regulations. Store in a segregated and approved area. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Keep out of reach of children. Store away from incompatible materials (see Section 10).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational exposure limits

Ingredient name	Exposure limits
Ethyl alcohol	<p>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 1000 ppm 8 hours. 8 hrs OEL: 1880 mg/m³ 8 hours.</p> <p>CA Quebec Provincial (Canada, 7/2019). TWAEV: 1000 ppm 8 hours. TWAEV: 1880 mg/m³ 8 hours.</p> <p>CA British Columbia Provincial (Canada, 1/2020). STEL: 1000 ppm 15 minutes.</p> <p>CA Ontario Provincial (Canada, 6/2019). STEL: 1000 ppm 15 minutes.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 1250 ppm 15 minutes. TWA: 1000 ppm 8 hours.</p>
propan-2-ol	<p>CA Alberta Provincial (Canada, 6/2018). 15 min OEL: 984 mg/m³ 15 minutes. 8 hrs OEL: 200 ppm 8 hours. 15 min OEL: 400 ppm 15 minutes. 8 hrs OEL: 492 mg/m³ 8 hours.</p> <p>CA British Columbia Provincial (Canada, 1/2020). TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes.</p> <p>CA Ontario Provincial (Canada, 6/2019). TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes.</p> <p>CA Quebec Provincial (Canada, 7/2019). TWAEV: 400 ppm 8 hours. TWAEV: 983 mg/m³ 8 hours. STEV: 500 ppm 15 minutes. STEV: 1230 mg/m³ 15 minutes.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 400 ppm 15 minutes. TWA: 200 ppm 8 hours.</p>
glycerol	<p>CA Alberta Provincial (Canada, 6/2018). Skin sensitizer. 8 hrs OEL: 10 mg/m³ 8 hours. Form: Mist</p> <p>CA Quebec Provincial (Canada, 7/2019). TWAEV: 10 mg/m³ 8 hours. Form: mist</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 20 mg/m³ 15 minutes. Form: mist TWA: 10 mg/m³ 8 hours. Form: mist</p> <p>CA British Columbia Provincial (Canada, 1/2020). TWA: 3 mg/m³ 8 hours. Form: respirable mist TWA: 10 mg/m³ 8 hours. Form: total mist</p>

Appropriate engineering controls For manufacturing or industrial uses it can be appropriate to: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilating equipment.

Individual protection measures

Eye/face protection	Continued or intense exposures might required to wear safety glasses.
Hands and Body protection	No specific protective equipment required under normal use conditions. No special protective clothing is required.
Respiratory protection	No specific protective equipment required under normal use conditions.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid.	pH	7.7	Flash point	Closed cup: 20 °C (68 °F) [Pensky-Martens]
Color	Colorless.	Relative density	0.88	Melting point	Not available.
Odor	Alcohol-like.	Viscosity	Kinematic: 57.5 cm ² /s (5750 cSt)	Boiling point	80 °C (176 °F)
Odor threshold	Not available.	Vapor pressure	Not available.	Fire point	: Not available.
Solubility in water	: Not available.	Vapor density	: Not available.	Evaporation rate	: Not available.
Decomposition temperature	: Not available.	Auto-ignition temperature	: Not available.		
Partition coefficient: n-octanol/ water	: Not applicable.	Flammability (solid, gas)	: Not available.		
Lower and upper explosive (flammable) limits	: Not available.				

10. STABILITY AND REACTIVITY

Reactivity	No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	The product is stable.
Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials
Conditions to avoid	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. TOXICOLOGICAL INFORMATION

Route of exposure	Not available.	
	<u>Potential acute health effects</u>	<u>Symptoms</u>
Eye contact	May cause eye irritation.	Adverse symptoms may include the following: irritation watering redness
Skin contact	No known significant effects or critical hazards.	No specific symptoms under normal use conditions.
Ingestion	No known significant effects or critical hazards.	No specific symptoms under normal use conditions.
Inhalation	No known significant effects or critical hazards.	No specific symptoms under normal use conditions.

Toxicity data

Product/ingredient name	Result	Species	Dose	Exposure
Ethyl alcohol	LC50 Inhalation Vapor	Rat	124700 mg/m ³	4 hours
	LD50 Dermal	Rabbit	>20000 mg/kg	-
	LD50 Oral	Rat	7 g/kg	-
propan-2-ol	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-
glycerol	LD50 Dermal	Rabbit	10946 mg/kg	-
	LD50 Oral	Mouse	4090 mg/kg	-
	LD50 Oral	Rat	12600 mg/kg	-

Information on toxicological effects

Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.
Sensitization	Not available.
Carcinogenicity	No known significant effects or critical hazards.

12. ECOLOGICAL INFORMATION

Ecotoxicity data


Product/ingredient name	Result	Species	Exposure
Ethyl alcohol	Acute EC50 17.921 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 2000 µg/l Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 25500 µg/l Marine water	Crustaceans - Artemia franciscana - Larvae	48 hours
	Acute LC50 42000 µg/l Fresh water	Fish - Oncorhynchus mykiss	4 days
	Chronic NOEC 4.995 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Chronic NOEC 100 µl/L Fresh water	Daphnia - Daphnia magna - Neonate	21 days
propan-2-ol	Chronic NOEC 0.375 µl/L Fresh water	Fish - Gambusia holbrooki - Larvae	12 weeks
	Acute EC50 7550 mg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 1400000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 4200 mg/l Fresh water	Fish - Rasbora heteromorpha	96 hours

Persistence and degradability : Unknown **Bioaccumulative potential** : Unknown **Mobility in soil** : Unknown **Other adverse effects** : Unknown

13. DISPOSAL CONSIDERATIONS

Disposal methods Dispose content and container in accordance with local, regional and national regulation in force.

14. TRANSPORT INFORMATION

	UN number	UN proper shipping name	Transport hazard class (es)	Packing group	TDG Placard
TDG Classification	UN1987	Alcohols, N.O.S. (Ethanol)	3	II	

Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).

Special provisions Limited quantity index 1L

Additional information See shipping documents for specific information on DOT, IMDG or IATA

15. REGULATORY INFORMATION

Canadian lists

Canadian NPRI The following components are listed: ethanol; isopropyl alcohol

CEPA Toxic substances None of the components are listed.

Canada inventory Not determined.

International lists

United States Not determined.

16. OTHER INFORMATION

Hazardous Material Information System (U.S.A.)

Health Hazard	0
Fire Hazard	3
Reactivity	0
Personal Protection	

Date of issue/Date of revision (YYYY-MM-DD) : 2023-01-31

Prepared by : Regulatory Affairs Department

Wood Wyant Canada Inc.
A division of Sani-Marc Group
42, rue de l'Artisan
Victoriaville, Québec
G6P 7E3
1-819-758-1541

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.